SECTION 01 4533 -STRUCTURAL TESTING AND SPECIAL INSPECTION SERVICES

PART 1 - GENERAL

1.01 SUMMARY

- A. Section summarizes the responsibility of the Contractor and the Testing/Inspection Agency in the performance of the testing/inspection specified in the Contract Documents.
- B. Neither the observations of the Design Professional in the administration of the contract, nor tests/inspections by the Testing/Inspection Agency, nor approvals by persons other than the Design Professional shall relieve the Contractor from his obligation to perform the work in accordance with the Contract Documents.
- C. Special Inspection reports and a final report in accordance with Section 1704.2.4 of the 2018 International Building Code shall be submitted to the Building Official prior to the time that phase of work is approved for occupancy.

1.02 REFERENCES

- A. ASTM D3740 Practice for Evaluation of Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction.
- B. ASTM E329 Recommended Practice for Inspection and Testing Agencies for Concrete, Steel, and Bituminous Materials as Used in Construction.
- C. American Council of Independent Laboratories Recommended Requirements for Independent Laboratories Qualifications.

1.03 SELECTION AND PAYMENT

- A. The Owner will select the Testing/Inspection Agency and will pay for the structural testing and special inspection services that are required by the Contract Documents.
- B. Contractor shall pay for any additional structural testing/inspection required for work or materials not complying with Contract Documents due to negligence or nonconformance.
- C. Contractor shall pay for any additional structural testing/inspection required for his convenience.

1.04 SUBMITTALS

D. Completed Contractor's Statement of Responsibility

1.05 QUALITY ASSURANCE

A. Testing/Inspection Agency Qualifications: In accordance with the Minimum Special Inspector Qualifications Table.

1.06 STRUCTURAL TESTING AND SPECIAL INSPECTION REQUIRED FORMS

- A. Specific structural testing and special inspection forms are included in this specification section as follows:
 - 1. Minimum Special Inspector Qualifications Table
 - 2. Statement of Special Inspections
 - 3. Schedule of Special Inspections
 - 4. Fabricator Certificate of Compliance
 - 5. Final Report of Special Inspection

PART 2 - MATERIALS

Not Used.

PART 3 - EXECUTION

3.01 STRUCTURAL PRECONSTRUCTION MEETING

A. A structural preconstruction meeting may be conducted at the construction site by the Design Professional to discuss quality issues. The parties involved may be the Architect, Structural Engineer, Contractor, Structural Testing/Inspection Agency, appropriate subcontractors, suppliers, and detailers.

3.02 STRUCTURAL TESTING/INSPECTION AGENCY'S RESPONSIBILITIES

- A. Cooperate with the Contractor and provide timely service.
- B. Upon arriving at the construction site, sign in and notify the Contractor of presence.
- C. Select the representative samples that are to be tested/inspected.
- D. Perform tests/inspections as outlined in Contract Documents, the applicable code referenced standards, and as directed by the Design Professional.
- E. Report work and materials not complying with Contract Documents immediately to the Contractor and Design Professional.
- F. Leave copies of field notes with the Contractor prior to leaving the construction site. Field notes shall include the message given to the Contractor, date, time of message, name of Contractor's representative informed, type and location of work or materials tested/inspected, whether the work or materials complies with Contract Documents and name of the Structural Testing/Inspection Agency's representative.

- G. Report and distribute results of tests/inspections promptly in the form of written reports as directed by the Design Professional.
- H. Promptly report any non-conforming work in separate discrepancy reports indicating description, location, reference to applicable Contract Documents, resolution or corrective action taken and date.
- I. Structural Testing/Inspection Agency shall not alter requirements of Contract Documents, approve or reject any portion of the work, or perform duties of the Contractor.
- J. Initial and date the "Date Completed" box in the Schedule of Special Inspections as the inspection and testing activities are completed.
- K. Submit a completed Final Report of Special Inspections at the completion of the special inspection activities.

3.03 CONTRACTOR'S RESPONSIBILITIES

- A. Provide copy of Contract Documents to the Structural Testing/Inspection Agency.
- B. Arrange the preconstruction meeting to discuss quality issues.
- C. Notify the Structural Testing/Inspection Agency 48 hours in advance of operations to allow assignment of personnel and scheduling of tests.
- D. Cooperate with Structural Testing/Inspection Agency and provide access towork.
- E. Provide samples of materials to be tested in required quantities.
- F. Furnish copies of mill test reports when requested.
- G. Provide storage space for Structural Testing/Inspection Agency's exclusive use, such as for storing and curing concrete testing samples.
- H. Provide labor to assist the Structural Testing/Inspection Agency in performing tests/inspections.

END OF SECTION

MINIMUM SPECIAL INSPECTOR QUALIFICATIONS TABLE

Minimum Qualifications (refer to key at end of					
Category of Testing and Inspection	Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports		
1704.2.5 Inspection of Fabricators					
1. Pre-cast concrete	A, C, E				
2. Structural steel construction	C, F, G				
3. Wood construction	A				
4. Cold formed metal construction	A				
1705.2, 1705.10, 1705.11& 1705.12 Steel Construction	ı				
Verification of welding consumables, filler metals, procedure specifications, procedure qualification records and personnel performance qualification records			C, F		
2. Nondestructive testing of welding	G	G			
3. Inspection of welding	C, F	C, F			
4. Verification of fabricator and erector documents as listed in AISC 360, chapter N, paragraph 3.2			A, C		
5. Material verification of weld fillermaterials			C, F		
6. Inspection of high strength bolting and steel frame joint details		A, C			
7. Inspection of embedments and erection of fabricated steel and steel frame elements		A, C, F			
8. Inspection of steel elements of composite construction		A, C, F			
Verification of reinforcing steel, cold formed steel deck and truss materials			A, C, F		
10. Inspection of reinforcing steel, cold formed steel deck and trusses		A, C			
1705.3 & 1705.12 Concrete Construction					
Reinforcing placement, cast-in-place bolts, post installed anchors concrete and shotcrete placement and curing operations. Inspection of formwork for shape, location and dimensions		A, C, H			
2. Pre-stressing steel installation		A, C, D, E			
3. Erection of pre-cast concrete members		A, C, H			
4. Concrete field sampling and testing		J			
5. Concrete strength testing		Р			
6. Review certified mill reports		A I I II C	A, C		
7. Verify use of required design mix		A, I, J, H, C			
8. Pre-stressed (pre-tensioned) concrete force application	A, C, E				
9. Post-tensioned concrete force application		A, C, D			
Review of in-situ concrete strength, prior to stressing of tendons in post-tensioned concrete and prior to removal of shores and forms from beams and structural slabs		A, C, D, H			
11. Reinforcing steel weldability, reinforcing welding, weld filler material		C, F			

(Table	Continued)		
	Minimum Qualific	cations (refer to key	
Category of Testing and Inspection	Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports
12. Testing of welding of reinforcing steel		G	
1705.4 Masonry			
1. Verification of f'm and f'AAC		A, C, L, M	
Mortar joint construction, grout protection and placement, materials proportion, type/size/location of reinforcement, structural elements, anchorage, and connectors		A, C, K	
3. Sampling/testing of grout/mortar specimens		A, C, L, M	
4. Observe preparation of masonry prisms for testing of compressive strength of masonry, $f'm$ and $f'AAC$		A, C, K, L, M	
5. Inspection of welding of reinforcing steel		C, F	
6. Testing of welding of reinforcing steel		G	
1705.6& 1804 Soils			
Observe site preparation, fill placement testing of compaction for compliance with the construction documents for the project		A, C, I, N	
Observe test bearing materials below shallow foundations for ability to achieve design bearing capacity		A, C, I, N (Level III)	
3. Review compaction testing for compliance with the construction documents for the project			A
1705.5, 1705.10, 1705.11 & 1705.12 Wood Construction	on		
Observe structural panel sheathing, size of framing members, nail or staple diameter and length, number of fastener lines, and spacing of fastener lines and fasteners for compliance with construction documents for the project		A	
2. Observe temporary and permanent truss member restraint/bracing, field gluing of elements. Observe bolting, anchoring or other fastening of: shear walls, diaphragms, drag struts, braces and hold-downs.		A	
1705.7, 1705.8, 1705.9 & 1810 Pile and Pier Foundation	ons		
1. Observe installation		A, N	
2. Observe load tests		A	
1705.13 Sprayed Fire-Resistant Materials			
Observe surface conditions, application, average thickness and density of applied material, and cohesive/adhesive bond		A, C	
1705.14 Mastic and Intumescent Fire-Resistant Coati	ngs		
1. Observe application compliance with AWCI 12- B		A, C	
1705.15 Exterior Insulation and Finish Systems			

(Table	Continued)				
	Minimum Qualifications (refer to key at end of Ta				
Category of Testing and Inspection	Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports		
1. Inspect EIFS systems		A, B, C, O			
1705.1 Special Cases					
1. Work of unusual or special nature		A, B, O			
1705.16 Fire-Resistant Penetrations and Joints	See Requirements o	f IBC Sections 1705. I	16.1 and 17016.2		
1705.17 Smoke Control	See Requirements o	f IBC Section .1705.1	7.2		
1705.10, 1705.11, 1705.12, Seismic and Wind Resistar	ıce				
Periodic inspection of fabrication, installation and/or anchorage of building systems and components		A			

KEY:

- A. Georgia Professional Engineer (GA PE) competent in the specific task area or graduate of accredited engineering/engineering technology program under the direct supervision of a GA PE.
- B. Georgia Registered Architect (GA RA) or graduate of accredited architecture/architecture technology program under the direction of a GA RA.
- C. International Code Council (ICC) Special Inspector Certification specific to the particular material and testing methodology applicable to each Category of Testing and Inspection listed in the table.
- D. Post-tensioning Institute (PTI) Certification, Level 2, bonded or unbonded as applicable.
- E. Pre-stressed Concrete Institute (PCI) Certified Inspector.
- F. American Welding Society (AWS) Certified Welding Inspector (CWI) or AWS Certified Associate Welding Inspector working under the direct on-site supervision of a CWI.
- G. American Society for Nondestructive Testing (ASNT) Level II certification, or a Level III certification if previously certified as a Level II in the particular material and testing methodology applicable to each Category of Testing and Inspection listed in the table.
- H. American Concrete Institute (ACI) Concrete Construction Special Inspector.
- National Institute for Certification in Engineering Technologies (NICET) Level II or higher certification specific to
 the particular material and testing methodology applicable to each Category of Testing and Inspection listed in the
 table.
- J. ACI Concrete Field Testing Technician with Grade 1 certification.
- K. Georgia Concrete and Products Association (GC&PA) Masonry Association of Georgia (MAG) Masonry Construction Inspector Certification.
- L. National Concrete Masonry Association (NCMA) Concrete Masonry Testing Procedures certification.
- M. GC&PA MAG Masonry Testing Technician certification.
- N. NICET Certified Engineering Technologist (CT).
- O. Other Qualified Special Inspector as approved by the Building Official.
- P. American Concrete Institute (ACI) Strength Testing Technician.

NOTES:

- 1. The Special Inspector shall meet one of the minimum qualifications listed for the applicable Category of Testing and Inspection.
- 2. Materials testing shall be done by an Approved Testing Agency meeting the requirements of IBC Section 1703 and ASTM E 329.

STATEMENT OF SPECIAL INSPECTIONS

PROJECT:	 	
LOCATION:		

PERMIT APPLICANT:					
APPLICANT'S ADDRESS:					
ARCHITECT OF RECORD:					
STRUCTURAL ENGINEER OF RECOR	RD: <u>Martin S. Kigudd</u>	e, PE			
MECHANICAL ENGINEERS OF RECO	ORD:				
ELECTRICAL ENGINEERS OF RECO	RD:	_			
REGISTERED DESIGN PROFESSIONA	AL IN RESPONSIBLI	E CHARGE:			
This Statement of Special Inspections is sub- includes a <i>Schedule of Special Inspection Se</i> individuals, agencies, or firms intended to be for Seismic Resistance and/or Special Inspec	rvices applicable to the eretained for conducting	above-referenced Prong these inspections. I	oject as well as tl	ne identity of t	the
Are Special Inspections for Seismic Resista	ance included in the Sta	tement of Special Ins	pections?	☐ Yes	⊠ No
Are Special Inspections for Wind Resistance		* *	•	☐ Yes	⊠ No
and to the Registered Design Professional in Building Official prior to the start of work. I correction. If the discrepancies are not corrections are professional in Responsibility inspections shall be submitted to the Buildin conclusion of the project. Frequency of interim report submittals to the	Discrepancies shall be bected, the discrepancies ble charge of special in a Official and the Region	orought to the immedi shall be brought to the spections and correcti stered Design Profess	iate attention of the attention of the ions of any discressional in Respons	he Contractor e Building Off epancies noted	for ficial and the lin the
		•	-		
WeeklyBi-Weekly	X Monthly	Other; specif	ry:		
The Special Inspection program does not rel Jobsite safety and means and methods of con				Contract Docui	ments.
Statement of Special Inspections Prepared by	y:	Γ	Prepare	er's Seal	
Martin S. Kigudde					
Type or print name					
Signature	Date				
Building Official's Acceptance:					
Signature	Date	<u>L</u>			
Permit Number:	2 412				
Frequency of interim report submittals to theMonthlyBi- Monthl		on Oth	ner; specify:		

SCHEDULE OF SPECIAL INSPECTIONS TABLE

Project					
	G.	Applicable to this Project			
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed
1704.2.5 Inspection of Fabricators Required where structural load-bearing membrabricator is approved in accordance with sect fabrication, the approved fabricator shall subravork was performed in accordance with the a	tion 1704.2.5.2. Who nit a certificate of co	ere this omplian	exception is utilizate to the building	ed, at the c	ompletion of
Verify fabrication/quality control procedures	In-plant review (3)	Y	Periodic	1	
1705.1.1 Special Cases					
Work unusual in nature, including but not limited to alternative materials and systems, unusual design applications, materials and systems with special manufacturer's requirements	Submittal review, shop (3) and/or field inspection	N			
2. Inspection of anchors post-installed in solid grouted masonry: Per research reports including verification of anchor type, anchor dimensions, hole dimensions, hole cleaning procedures, anchor spacing, edge distances, masonry unit, grout, masonry compressive strength, anchor embedment and tightening torque	Field inspection	Y	Periodic or as required by the research report issued by an approved source	1	
1705.2 Steel Construction Special inspection of the steel fabrication p welding, thermal cutting or heating operation					not perform any
Fabricator and erector documents (Verify reports and certificates as listed in AISC 360, chapter N, paragraph 3.2 for compliance with construction documents)	Submittal Review	Y	Each submittal	1	
2. Material verification of structural steel	Shop (3) and field inspection	Y	Periodic	1	
3. Embedments (Verify diameter, grade, type, length, embedment. See 1705.3 for anchors)	Field inspection	Y	Periodic	1	
4. Verify member locations, braces, stiffeners, and application of joint details at each connection comply with construction documents	Field inspection	Y	Periodic	1	

	(Table Continued)				
Project		ı			• .
Material / Activity	Service	Y/N	Applicable Extent	Agent*	Date Completed
5. Structural steel welding:					•
a. Inspection tasks Prior to Welding (Observe, or perform for each welded joint or member, the QA tasks listed in AISC 360, Table N5.4-1)	Shop (3) and field inspection	Y	Observe or Perform as noted (4)	1	
b. Inspection tasks During Welding (Observe, or perform for each welded joint or member, the QA tasks listed in AISC 360, Table N5.4-2)	Shop (3) and field inspection	Y	Observe (4)	1	
c. Inspection tasks After Welding (Observe, or perform for each welded joint or member, the QA tasks listed in AISC 360, Table N5.4-3)	Shop (3) and field inspection	Y	Observe or Perform as noted (4)	1	
d. Nondestructive testing (NDT) of welded joints: As a minimum for special inspections, AISC 360 Chapter N requires UT testing of complete joint penetration groove welds (CJP) subject to transversely applied tension loading in butt, T- and corner joints, in materials 5/16" (8mm) thick or greater. Further NDT testing, including UT testing of partial penetration groove welds (PJP) and magnetic particle or penetrant testing of fillet welds, may be added at the option of the engineer of record as a project requirement. AISC 360 Chapter N also allows reduction or increase in the rate of UT testing if approved by the engineer of record and by the authority having jurisdiction.					
1) Complete penetration groove welds 5/16" or greater	Shop (3, 5) or field ultrasonic testing - 100%	Y	Periodic	1	
2) Thermally cut surfaces of access holes when material t > 2"	Shop (3) or field magnetic Particle or Penetrant testing	Y	Periodic	1	

(Table Continued)					
Project					
N. (. 1 / A /	g ·		Applicable	to this Pro	oject
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed
3) Welded joints subject to fatigue when required by AISC 360, Appendix 3, Table A-3.1 This requirement is intended to apply when the flange thickness of rolled shapes exceeds 2" or when the web thickness of built up shapes exceeds 2". Any crack shall be deemed unacceptable regardless of size or location.	Shop (3) or field radiographic or Ultrasonic testing	N	Periodic	1	
4) Fabricator's NDT reports when fabricator performs NDT NDT of welds completed in an approved fabricator's shop may be performed by that fabricator only when approved by the authority having jurisdiction. Special Inspections include review of reports of all NDT testing done by the fabricator.	Verify reports	Y	Each submittal (5)	1	
6. Structural steel bolting:	Shop (3) and field inspection				
a. Inspection tasks Prior to Bolting (Observe, or perform tasks for each bolted connection, in accordance with QA tasks listed in AISC 360, Table N5.6-1)		N	Observe or Perform as noted (4)	1	
b. Inspection tasks During Bolting (Observe the QA tasks listed in AISC 360, Table N5.6-2)		Y	Observe (4)	1	
Pre-tensioned and slip-critical joints					
a) Turn-of-nut with matching markings		N	Periodic		
a) Direct tension indicator		Y	Periodic	1	
b) Twist-off type tension control bolt		Y	Periodic	1	
c) Turn-of-nut without matching markings		N	Continuous		
d) Calibrated wrench		N	Continuous		
2) Snug-tight joints		N	Periodic		

	(Table Continued)				
Project					
Madanial / Andrida	Applicable to this Proje		oject		
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed
c. Inspection tasks After Bolting (Perform tasks for each bolted connection in accordance with QA tasks listed in AISC 360, Table N5.6-3)		Y	Perform (4)	1	
7. Inspection of steel elements of composite construction prior to concrete placement in accordance with QA tasks listed in AISC 360, Table N6.1	Shop (3) and field inspection and testing	Y	Observe or Perform as noted (4)	1	
1705.2.2 Steel Construction Other Than St	ructural Steel				
Material verification of cold-formed steel deck:					
a. Identification markings	Field inspection	Y	Periodic	1	
b. Manufacturer's certified test reports	Submittal Review	N	Each submittal		
Connection of cold-formed steel deck to supporting structure:	Shop (3) and field inspection				
a. Welding					
Per AWS D1.3.		Y	Periodic	1	
b. Other fasteners (in accordance with AISC 360,Section N6)					
Verify fasteners are in conformance with approved submittal		Y	Periodic	1	
Verify fastener installation is in conformance with approved submittal and manufacturer's recommendations		Y	Periodic	1	
3. Reinforcing steel Per AWS D1.4 and ACI 318 Section 3.5.2.	Shop (3) and field inspection				
a. Verification of weldability of steel other than ASTM A706		N	Periodic		
b. Reinforcing steel resisting flexural and axial forces in intermediate and special moment frames, boundary elements of special concrete structural walls and shear reinforcement		N	Continuous		
c. Shear reinforcement		N	Continuous		
d. Other reinforcing steel		N	Periodic		

a. Application of prestressing force

	(Table Continu	ıed)			
Project					
			Applicable	to this Pro	oject
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed
4. Cold-formed steel trusses spanning 60 feet or greater					
 a. Verify temporary and permanent restraint/bracing are installed in accordance with the approved truss submittal package 	Field inspection	N	Periodic		
1705.3 Concrete Construction Special Inspections are not required for cert nonstructural concrete slabs supported direct with Table 1807.1.6.2. See Section 1705.3 f concrete patios, driveways and sidewalks, of the concrete pation of reinforcing steel	tly on the ground, and or these specific exce	d concr	ete foundation wa	lls construc	eted in accordan
installation (see 1705.2.2 for welding)	field inspection	Y	Periodic.	1	
Inspection of prestressing steel installation	Shop (3) and field inspection	N	Periodic		
3. Inspection of anchors cast in concrete where allowable loads have been increased per section 1908.5 or where strength design is used	Shop (3) and field inspection	N	Periodic		
4. Inspection of anchors and reinforcing steel post-installed in hardened concrete: Per research reports including verification of anchor type, anchor dimensions, hole dimensions, hole cleaning procedures, anchor spacing, edge distances, concrete minimum thickness, anchor embedment and tightening torque	Field inspection	Y	Periodic or as required by the research report issued by an approved source	1	
5. Verify use of approved design mix	Shop (3) and field inspection	Y	Periodic	1	
6. Fresh concrete sampling, perform slump and air content tests and determine temperature of concrete	Shop (3) and field inspection	Y	Continuous	1	
7. Inspection of concrete and shotcrete placement for proper application techniques	Shop (3) and field inspection	Y	Continuous	1	
8. Inspection for maintenance of specified curing temperature and techniques	Shop (3) and field inspection	Y	Periodic	1	
9. Inspection of prestressed concrete	Shop (3) and field inspection	N			
a Application of prostrossing force	-	Νī			Ī

Continuous

	(Table Continu	ied)			
Project					
Material / Activity	Service		Applicable		oject Date
		Y/N	Extent	Agent*	Completed
b. Grouting of bonded prestressing tendons in the seismic-force- resisting system		N	Continuous		
c. Verify proper installation of encapsulation caps and grouting of pocket recesses.		N	Continuous		
10. Erection of precast concrete members					
Inspection of the erection of precast concrete has always been included in IBC, but no specific inspections have been indicated. Inspection of bolts and welds for precast concrete are covered in Section 1705.2 Steel Construction. Any specific precast erection inspection requirements should either be added to the project Special Inspection Schedule or Construction Documents. The following are some inspections that the Design Professional should consider:					
A. Verify member locations and joint details comply with construction and erection documents					
B. Verify proper bearing pad type and placement					
C. Verify placement of grout (including hot and cold weather procedures and that max. specified number of levels to be placed before grouting are not exceeded					
D. Verify joint widths are within specified tolerance where joints are to receive sealant					
E. Verify thread engagement and torque for mechanical connections					

	(Table Continu	ued)			
Project					
Nr.4	G		Applicable	to this Pro	ject
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed
a. Inspect in accordance with construction documents	Field inspection	N	In accordance with construction documents		
b. Perform inspections of welding and bolting in accordance with Section 1705.2	Field inspection	N	In accordance with Section 1705.2		
c. Application of joint details at each connection	Field inspection	N	Periodic		
11. Verification of in-situ concrete strength, prior to stressing of tendons in post tensioned concrete and prior to removal of shores and forms from beams and structural slabs	Review field testing and laboratory reports	N	Periodic		
12. Inspection of formwork for shape, lines, location and dimensions	Field inspection	N	Periodic		
13. Testing of concrete floor flatness as required per construction documents.	Field testing	Y	Periodic	1	
14. Concrete strength testing and verification of compliance with construction documents	Field testing and review of laboratory reports	Y	Periodic	1	
1705.4 Masonry Construction Masonry construction shall be inspected and 602/ACI 530.1/ASCE 6 quality assurance pro		ce with	TMS 402/ACI 53	0/ASCE 5 a	and TMS
Exceptions: See 1705.5 Risk					
Categories: See 1604.5					

(A) Level A, B + C Quality Assurance: Masonry in Risk Category I, II, or III structures and designed in accordance with ACI 530 Chapter 5, 6, or 7 (Empirical Design, Veneer, Glass Unit Masonry)					
Verify compliance with approved submittals	Field Inspection	Y	Periodic	1	
(B) Level B Quality Assurance: 1. Masonry in Risk Category IV structures and designed in accordance with ACI 530 Chapter 6 or 7 (Veneer, Glass Unit Masonry)					

	(Table Continu	ied)			
Project		1			
Material / Activity	Service		Applicable		oject Date
·		Y/N	Extent	Agent*	Completed
2. Masonry in Risk Category I, II, or III structures and designed in accordance with ACI 530 Chapter 2, 3, 4, 8 or Appendix B (Allowable Stress Design, Strength Design, Prestressed Masonry, AAC Masonry, Masonry Infill)					
Verification of fm and fAAC prior to construction	Testing by unit strength method or prism test method	Y	Periodic	1	
(C) Level C Quality Assurance: Masonry in Risk Category IV structures and designed in accordance with ACI 530 Chapter 2, 3, 4, 8 or Appendix B (Allowable Stress Design, Strength Design, Prestressed Masonry, AAC Masonry, Masonry Infill)					
Verification of fm and fAAC prior to construction and for every 5,000 SF during construction	Testing by unit strength method or prism test method	N	Periodic		
2. Verification of proportions of materials in premixed or preblended mortar, prestressing grout, and grout other than self-consolidating grout, as delivered to the project site	Field inspection	N	Continuous		
3. Verify placement of masonry units	Field Inspection	N	Periodic		
(D) Levels B + C Quality Assurance:					
Verification of Slump Flow and Visual Stability Index (VSI) of self-consolidating grout as delivered to the project	Field testing	Y	Continuous	1	
Verify compliance with approved submittals	Field inspection	Y	Periodic	1	
Verify proportions of site-mixed mortar, grout and prestressing grout for bonded tendons	Field Inspection	Y	Periodic	1	
Verify grade, type, and size of reinforcement and anchor bolts, and prestressing tendons and anchorages	Field Inspection	Y	Periodic	1	
5. Verify construction of mortar joints	Field Inspection	Y	Periodic	1	

(Table Continued)						
Project						
Material / Activity	Service		Applicable		oject Date	
·		Y/N	Extent	Agent*	Completed	
Verify placement of reinforcement, connectors, and prestressing tendons	Field Inspection	Y	Level B - Periodic	1		
and anchorages	inspection	N	Level C - Continuous			
7. Verify grout space prior to grouting	Field	Y	Level B - Periodic	1		
78 1 1 8 8	Inspection	N	Level C - Continuous			
Verify placement of grout and prestressing grout for bonded tendons	Field Inspection	Y	Continuous	1		
Verify size and location of structural masonry elements	Field Inspection	Y	Periodic	1		
10. Verify type, size, and location of anchors, including details of anchorage of masonry to structural	Field inspection	Y	Level B - Periodic	1		
members, frames, or other construction.	r icid inspection	N	Level C - Continuous			
11. Verify welding of reinforcement (see 1705.2.2)	Field inspection	N	Continuous			
12. Verify preparation, construction, and protection of masonry during cold weather (temperature below 40°F) or	Field inspection	Y	Periodic	1		
hot weather (temperature above 90°F) 13. Verify application and measurement of prestressing force	Field Inspection	N	Continuous			
14. Verify placement of AAC masonry units and construction of thin-bed mortar joints (first 5000 SF of AAC masonry)	Field inspection	N	Continuous			
15. Verify placement of AAC masonry units and construction of thin-bed	Field inspection	N	Level B - Periodic			
mortar joints (after the first 5000 SF of AAC masonry)		N	Level C - Continuous			
16. Verify properties of thin-bed mortar for AAC masonry (first 5000 SF of AAC masonry)	Field inspection	N	Continuous			
17. Verify properties of thin-bed mortar for AAC masonry (after the first 5000 SF	Field	N	Level B - Periodic			
of AAC masonry)	inspection	N	Level C - Continuous			
18. Prepare grout and mortar specimens	Field testing	Y	Level B - Periodic	1		
10. Frequie grout and mortal specimens		N	Level C - Continuous			
19. Observe preparation of prisms	Field inspection	Y	Level B -	1		

(Table Continued)							
Project							
			Applicable	to this Pro	ject		
Material / Activity	Service	Y/N Extent	Extent	Agent*	Date Completed		
			Periodic				
		N	Level C - Continuous				

1705.5 Wood Construction

Special inspections of the fabrication process of prefabricated wood structural elements and assemblies shall be in accordance with Section 1704.2.5. High-load diaphragms designed in accordance with Section 2306.2 shall be installed with special inspections as indicated in Section 1704.2.

Exception: Special inspections are not required for portions of structures designed and constructed in accordance with IBC Section 2308 unless the approved construction documents indicate otherwise.

Inspection of the fabrication process of wood structural elements and assemblies in accordance with Section 1704.2.5	In-plant review (3)	N	Periodic	
2. For high-load diaphragms, verify grade and thickness of structural panel sheathing agree with approved building plans	Field inspection	N	Periodic	
3. For high-load diaphragms, verify nominal size of framing members at adjoining panel edges, nail or staple diameter and length, number of fastener lines, and that spacing between fasteners in each line and at edge margins agree with approved building plans	Field inspection	N	Periodic	
Verify grade of lumber, manufactured wood products and sheathing.	Field inspection	N	Periodic	
5. Inspect details of wood framing including member types, sizes, spacing, blocking, bridging and bearing.	Field inspection	N	Periodic	
6. Inspect wood connections including nailing, bolting, tie downs, hangers and anchors.	Field inspection	N	Periodic	
7. Inspect diaphragms for sheathing thickness and for fastener size and spacing.	Field inspection	N	Periodic	

	(Table Continu	ıed)					
Project							
Material / Activity	Service		Applicable to this Project				
Waterial / Activity	Service	Y/N Extent	Extent	Agent*	Date Completed		
8. Metal-plate-connected wood trusses spanning 60 feet or greater: verify temporary and permanent restraint/bracing are installed in accordance with the approved truss submittal package	Field inspection	N	Periodic				
1705.6 Soils The approved geotechnical report and the conshall be used to determine compliance. Wherefor fill placement, the special inspector shall percent of the maximum dry density at op	e Section 1803 does verify that the in-pla	not req	uire reporting of r density of the com	naterials ar	d procedures is not less than		
Verify materials below shallow foundations are adequate to achieve the design bearing capacity.	Field inspection	Y	Periodic	1			
Verify excavations are extended to proper depth and have reached proper material.	Field inspection	Y	Periodic	1			
3. Perform classification and testing of controlled fill materials.	Field inspection	Y	Periodic	1			
Verify use of proper materials, densities, and lift thicknesses during placement and compaction of controlled fill	Field inspection	Y	Continuous	1			
5. Prior to placement of controlled fill, observe subgrade and verify that site has been prepared properly	Field inspection	Y	Periodic	1			
1705.7 Driven Deep Foundations The approved geotechnical report, and the coshall be used to determine compliance.	nstruction document	s prepa	red by the registe	red design _l	professionals,		
Verify element materials, sizes and lengths comply with requirements	Field inspection	N	Continuous				
Determine capacities of test elements and conduct additional load tests, as required	Field inspection	N	Continuous				
Observe driving operations and maintain complete and accurate records for each element	Field inspection	N	Continuous				

(Table Continued)					
Project					
Material / Activity	Service		Applicable	to this Pro	
		Y/N	Extent	Agent*	Date Completed
4. Verify placement locations and plumbness, confirm type and size of hammer, record number of blows per foot of penetration, determine required penetrations to achieve design capacity, record tip and butt elevations and document any damage to foundation element	Field inspection	N	Continuous		
5. For steel elements, perform additional inspections per Section 1705.2	See Section 1705.2	N	See Section 1705.2		
6. For concrete elements and concrete- filled elements, perform additional inspections per Section 1705.3	See Section 1705.3	N	See Section 1705.3		
7. For specialty elements, perform additional inspections as determined by the registered design professional in responsible charge	Field inspection	N	In accordance with construction documents		
8. Perform additional inspections and tests in accordance with the construction documents	Field Inspection and testing	N	In accordance with construction documents		
1705.8 Cast-in-Place Deep Foundations The approved geotechnical report, and the conshall be used to determine compliance.	nstruction document	s prepa	red by the register	red design p	professionals,
Observe drilling operations and maintain complete and accurate records for each element	Field inspection	N	Continuous		
2. Verify placement locations and plumbness, confirm element diameters, bell diameters (if applicable), lengths, embedment into bedrock (if applicable) and adequate end-bearing strata capacity. Record concrete or grout volumes	Field inspection	N	Continuous		
3. For concrete elements, perform additional inspections in accordance with Section 1705.3	See Section 1705.3	N	See Section 1705.3		
Perform additional inspections and tests in accordance with the construction documents	Field Inspection and testing	N	In accordance with construction documents		_
1705.9 Helical Pile Foundations					

(Table Continued)									
Project									
			Applicable	Applicable to this Project					
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed				
The approved geotechnical report, and the construction documents prepared by the registered design professional, shall be used to determine compliance.									
Verify installation equipment, pile dimensions, tip elevations, final depth, final installation torque and other data as required.	Field inspection	N	Continuous						
Perform additional inspections and tests in accordance with the construction documents	Field Inspection and testing	N	In accordance with construction documents						
1705.10.1 Structural Wood Special Inspections For WindResistance									
Inspection of field gluing operations of elements of the main windforceresisting system	Field inspection	N	Continuous						
Inspection of nailing, bolting, anchoring and other fastening of components within the main windforce-resisting system	Shop (3) and field inspection	N	Periodic						
1705.10.2 Cold-formed Steel Special Inspec	ctions For Wind Re	sistanc	e						
Inspection during welding operations of elements of the main windforceresisting system	Shop (3) and field inspection	N	Periodic						
2. Inspections for screw attachment, bolting, anchoring and other fastening of components within the main windforce-resisting system	Shop (3) and field inspection	N	Periodic						
1705.10.3 Wind-resisting Components									
1. Roof cladding	Shop (3) and field inspection	N	Periodic						
2. Wall cladding	Shop (3) and field inspection	N	Periodic						

1705.11.1 Structural Steel Special Inspections for Seismic Resistance

Mandatory in accordance with AISC 341 for the seismic force-resisting systems in Seismic Design Category C, D, E or F

Exceptions:

1. Structures assigned to Seismic Design Category C with structural steel systems not specifically detailed for seismic resistance with a Response Modification Coefficient, R, of 3 or less, excluding cantilever column systems.

	(Table Continu	ied)							
Project									
	G .		Applicable	to this Pro	oject				
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed				
2. Exceptions listed in Sections 1704.2 and 1705.11.									
Inspection of structural steel in accordance with AISC 341	Shop (3) and field inspection	N	In accordance with AISC 341						
 1705.11.2 Structural Wood Special Inspections for Seismic Resistance Mandatory for the seismic force-resisting systems in Seismic Design Category C, D, E or F. Exceptions: 1. Special inspection is not required for wood shear walls, shear panels and diaphragms, including nailing, bolting, anchoring and other fastening to other components of the seismic force-resisting system, where the fastener spacing of the sheathing is more than 4 inches oncenter. 2. Exceptions listed in Sections 1704.2 and 1705.11. 									
Inspection of field gluing operations of elements of the seismic-force resisting system	Field inspection	N	Continuous						
2. Inspection of nailing, bolting, anchoring and other fastening of components within the seismic-force- resisting system	Shop (3) and field inspection	N	Periodic						
1705.11.3 Cold-formed Steel Light-Frame Construction Special Inspections for Seismic Resistance Mandatory for the seismic-force-resisting systems in Seismic Design Category C, D, E or F. Exceptions: 1. Sheathing is gypsum board or fiberboard. 2. Sheathing is wood structural panel or steel sheet on only one side and the fastener spacing of the sheathing is more than 4 inches on center. 3. Exceptions listed in Sections 1704.2 and 1705.11.									
Inspection during welding operations of elements of the seismic-forceresisting system	Shop (3) and field inspection	N	Periodic						
2. Inspections for screw attachment, bolting, anchoring and other fastening of components within the seismic- force-resisting system	Shop (3) and field inspection	N	Periodic						
1705.11.4 Designated Seismic Systems Veri	fication								

(Table Continued)									
Project									
	~ .	Applicable to this Proje		oject					
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed				
Definition, Designed Seismic Systems: Those nonstructural components that require design in accordance with ASCE 7 Chapter 13 and for which the component importance factor, Ip, is greater than 1 in accordance with ASCE 7 Section 13.1.3.									
Inspect and verify that that the component label, anchorage or mounting conforms to the certificate of compliance in accordance with Section 1705.12.3 Mandatory for structures assigned to Seismic Design Category C, D, E or F.	Field inspection	N	Periodic						
1705.11.5 Architectural Components Specia	al Inspections for S	eismic	Resistance						
1. Inspection during the erection and fastening of exterior cladding and interior and exterior veneer Mandatory for structures assigned to Seismic Design Category D, E or F. Exceptions: 1. Not required for exterior cladding, interior and exterior nonbearing walls, and interior and exterior veneer 30 feet or less in height above grade or walking surface. 2. Not required for exterior cladding and interior and exterior veneers weighing 5 psf or less. 3. Not required for interior nonbearing walls weighing less than 15 psf.	Field inspection	Z	Periodic						
Inspection during the erection and fastening of interior and exterior nonbearing walls	Field inspection	N	Periodic						
3. Inspection during anchorage of access floors Mandatory for structures assigned to Seismic Design Category D, E or F. 1705 11 6 Machanical and Electrical Company.	Field inspection	N	Periodic	etoras					
1705.11.6 Mechanical and Electrical Comp	onents Special Insp	ections	s for Seismic Resi	stance					

(Table Continued)					
Project		ı			
Material / Activity	Service		Applicable		oject Date
		Y/N	Extent	Agent*	Completed
Inspection during the anchorage of electrical equipment for emergency or standby power systems Mandatory for structures assigned to Seismic Design Category C, D, E or F.	Field inspection	N	Periodic		
Inspection during the anchorage of other electrical equipment					
Mandatory for structures assigned to Seismic Design Category C, D, E or F.	Field inspection	N	Periodic		
Inspection during installation and anchorage of piping systems designed to carry hazardous materials, and their associated mechanical units Mandatory for structures assigned to Seismic Design Category C, D, E or F.	Field inspection	N	Periodic		
4. Inspection during the installation and anchorage of HVAC ductwork that will contain hazardous materials Mandatory for structures assigned to Seismic Design Category C, D, E or F.	Field inspection	N	Periodic		
Inspection during the installation and anchorage of vibration isolation systems Mandatory for structures assigned to Seismic Design Category C, D, E or F, where the construction documents require a nominal clearance of 0.25 inches or less, between the equipment support frame and restraint.	Field inspection	N	Periodic		
1705.11.7 Storage Racks Special Inspection	s for Seismic Resis	tance			
Inspection during the anchorage of storage racks 8 feet or greater in height Mandatory for structures assigned to Seismic Design Category D, E or F.	Field inspection	N	Periodic		
1705.11.8 Seismic Isolation Systems					

(Table Continued)								
Project								
	a .		Applicable	to this Pro	oject			
Material / Activity	Service	Y/N	Extent	Agent*	Date Completed			
Inspection during the fabrication and installation of isolator units and energy dissipation devices used as part of the seismic isolation system See ASCE 7 Section 17 for additional inspection and quality control requirements.	Shop and field inspection	N	Periodic					
1705.12.1 Concrete Reinforcement Testing and Qualification for SeismicResistance Applies to special moment frames, special structural walls, and coupling beams connecting special structural walls in structures assigned to Seismic Design Category B, C, D, E or F. The reinforcement shall comply with ACI 318 Section 21.1.5.2, and if it is to be welded, also determine weldability in accordance with ACI 318 Section 3.5.2.								
Review certified mill test reports for each shipment of reinforcement used to resist earthquake-induced flexural and axial forces in reinforced concrete special moment frames, special structural walls, and coupling beams connecting special structural walls	Review certified mill test reports	N	Each shipment					
2. Verify reinforcement weldability of ASTM A615 reinforcement used to resist earthquake-induced flexural and axial forces in reinforced concrete special moment frames, special structural walls, and coupling beams connecting special structural walls	Review test reports	N	Each shipment					
1705.12.2 Structural Steel Testing and Qualification for Seismic Resistance Applies to structural steel systems designed to AISC 341 and assigned to Seismic Design Category C, D, E or F. This is not required for steel structures assigned to Seismic Design Category C that are not specifically detailed for seismic resistance, with a response modification coefficient, R, of 3 or less, excluding cantilever column systems.								
Test in accordance with the quality assurance requirements of AISC 341	Shop (3) and field testing	N	Per AISC 341					
1705.12.3 Seismic Certification of Nonstructural Components Applies to architectural, mechanical and electrical components in structures assigned to Seismic Design Category C, D, E or F and where the requirements of ASCE 7 Section 13.2.1 are met by submittal of manufacturer's certification, in accordance with Item 2.								
Review certificate of compliance for designated seismic system components.	Certificate of compliance review	N	Each submittal					

	(Table Continu	ied)			
Project					
Material / Activity	Service	Applicable to this Project Date			
		Y/N	Extent	Agent*	Completed
Review the construction documents for the requirements for certification by analysis, testing or experience data for nonstructural components and designated seismic systems in accordance with ASCE 7 Section 13.2.					
1705.12.4 Seismic Isolation Systems					
Test in accordance with ASCE 7 Section 17.8	i.				
Test seismic isolation system in accordance with ASCE 7 Section 17.8	Prototype testing	N	Per ASCE 7		
Inspect in accordance with ASTM E 605, AS 1. Verify surface condition preparation of structural members	TM E 736, and the v	vritten i N	instructions of app	proved man	ufacturers.
Verify application of sprayed fire-	F' 11' 4'	N	D : 1:		
resistant materials	Field inspection	N	Periodic		
3. Verify average thickness of sprayed fire-resistant materials applied to structural members Thickness testing required for minimum of 25% of structural members on each floor. See Section 1705.13 for testing requirements for floor, roof and wall assemblies.	Field inspection	N	Periodic		
Verify density of the sprayed fire- resistant material complies with approved fire-resistant design	Field inspection and testing	N	Per IBC Section 1705.13.5		
5. Verify the cohesive/adhesive bond strength of the cured sprayed fire-resistant material	Field inspection and testing	N	Per IBC Section 1705.13.6		
1705.14 Mastic and Intumescent Fire-Resis	stant Coatings				
I. Inspect mastic and intumescent fire- resistant coatings applied to structural elements and decks Special inspections shall be in accordance with AWCI 12-B. Special inspections shall be based on	Field inspection	N	Periodic		

	(Table Contin	ued)			
Project					
	Service	Applicable to this Project			
Material / Activity		Y/N	Extent	Agent*	Date Completed
the fire-resistance design as designated in the approved construction documents.					
1705.15 Exterior Insulation and Finish Sys	tems (EIFS)				
Verify materials, details and installations are per the approved construction documents					
Mandatory except for applications installed over masonry or concrete walls, or where installed over a water-resistive barrier with means of draining moisture to the exterior.	Field inspection	N	Periodic		
Inspection of water-resistive barrier over sheathing substrate Mandatory where water-resistive barrier	Field inspection	N	Periodic		
coating is installed over sheathing substrate.					
1705.16 Fire-Resistant Penetrations and Jo Mandatory in high-rise buildings or in building 1604.5.		Catego	ory III or IV in acc	cordance w	rith Section
Inspect penetration firestop systems	Field testing	Y	Per ASTM E2174	1	
2. Inspect fire-resistant joint systems	Field testing	Y	Per ASTM E2393	1	
1705.17 Smoke Control Systems					
Mandatory by special inspection agencies have certification as air balancers.	ving expertise in fire	protec	tion engineering,	mechanical	engineering and
Leakage testing and recording of device locations prior to concealment	Field testing	N	Periodic		
Prior to occupancy and after sufficient completion, pressure difference testing, flow measurements, and detection and control verification	Field testing	N	Periodic		
* INSPECTION AGENTS	FIRM		ADDRE	SS	PHONE NO.
1. Qualified Testing Agent (TBD)					
2. Sykes Consulting Inc.					
3.					
4.					
NOTES:					
1. The inspection and testing agent(s) shall	be engaged by the	Owner o	or the Owner's Ag	ent, and	

	(Table Continu	ied)			
Project	(Table Contine	icuj			
	Service	Applicable to this Project			
Material / Activity		Y/N	Extent	Agent*	Date Completed
not by the Contractor or Subcontractor disclosed to the Building Official prior and/or testing agencies may be subject to the list of Special Inspectors may be sufficient as Special Inspections as required by Section accordance with IBC Section 1704.2.5.2.4. Observe on a random basis, operations at tasks for each welded joint, bolted connections of the substitution of the substitutio	r to commencing we to the approval of the bmitted as a separate on 1704.2.5 are not on the delayed pection, or steel element fabricator's shop shop shop to the control of	ork. The Buildie documente	e qualifications of ing Official and/o nent, if noted so a od where the fabri g these inspection	of the Speci r the Design bove. cator is app s. Perform	ial Inspector(s) n Professional. proved in these
Are Requirements for Seismic Resistance incl Are Requirements for Wind Resistance include			-	Yes Yes	⊠ No ⊠ No
			DA	ГЕ:	

FINAL REPORT OF SPECIAL INSPECTIONS

PROJECT:	
LOCATION:	
PERMIT APPLICANT:	
APPLICANT'S ADDRESS:	
ARCHITECT OF RECORD:	
STRUCTURAL ENGINEER OF RECORD:	
MECHANICAL ENGINEERS OF RECORD	
ELECTRICAL ENGINEERS OF RECORD:	
REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE:	
To the best of my information, knowledge, and belief, which are based upon observations or diligent su inspection services for the above-referenced Project, I hereby state that the special inspections or testing this Project, and designated for this Agent in the Schedule of Special Inspection Services, have been conaccordance with the Contract Documents.	required for
The Special Inspection program does not relieve the Contractor of the responsibility to comply with the Documents. Jobsite safety and means and methods of construction are solely the responsibility of the C	Contract ontractor.
Interim reports submitted prior to this final report and numbered to form a basis for, and a considered an integral part of this final report. The following discrepancies that were outstanding since interim report dated have been corrected:	
(Attach $8 \frac{1}{2}$ "x11" continuation sheet(s) if required to complete the description of corrections)	
Prepared By:	
Special Inspection Agent/Firm	
Type or print name	
Signature	